

Four Contact thin section ball bearing


 洛阳盟拓轴承科技有限公司
 Louyang Monton Bearing Science&Technology Co.Ltd.

Metric Stainless Steel Type Four Contact thin section ball bearing



Bearing Number	Dimensions (mm)				Capacities						Weight (kg)
	Size (mm)		Land Diameters (mm)		Radial		Thrust		Torque (N-m)		
	Bore	OD	L1	L2	Dynami c	Static	Dynami c	Static	Dynami c	Static	
K36020 XP0	360	400	375	385	8581	4518	21452	7408	15988	6316	2.73
K34020 XP0	340	380	355.0	365.0	8144	4388	20361	7154	14376	5812	2.58
K32020 XP0	320	360	335.0	345.0	7708	4255	19270	6897	12850	5323	2.44
K30020 XP0	300	340	315.0	325.0	7272	4119	18179	6633	11410	4849	2.30
K25020 XP0	250	290	265.0	275.0	6108	3731	15271	5906	8087	3706	2.10
K20020 XP0	200	240	215.0	225.0	4945	3309	12362	5130	5334	2678	1.57
K19020 XP0	190	230	205.0	215.0	4800	3260	11999	5029	4942	2519	1.51
K18020 XP0	180	220	195.0	205.0	4508	3143	11271	4823	4421	2312	1.44
K17020 XP0	170	210	185.0	195.0	4363	3023	10907	4719	3929	2113	1.37
K16020 XP0	160	200	175.0	185.0	4072	2970	10180	4507	3594	1967	1.30
K15020 XP0	150	190	165.0	175.0	3781	2845	9453	4290	3152	1779	1.22
K14020 XP0	140	180	155.0	165.0	3636	2791	9090	4179	2852	1643	1.15
K13020 XP0	130	170	145.0	155.0	3345	2660	8363	3953	2460	1468	1.07
K12020 XP0	120	160	135.0	145.0	3200	2603	7999	3837	2196	1341	1.01
K11020 XP0	110	150	125.0	135.0	2909	2466	7272	3601	1854	1179	0.94
K10020 XP0	100	140	115.0	125.0	2618	2323	6545	3357	1540	1026	0.87
K09020	90	130	105.0	115.0	2473	2263	6181	3231	1334	916	0.80

XP0											
K08020 XP0	80	120	95	105.0	2181	2111	5454	2973	1070	777	0.73
K07020 XP0	70	110	85	95.0	2071	2050	5090	2839	899	679	0.66
K06020 XP0	60	100	75	85.0	1906	1887	4363	2562	685	556	0.59

Bearing Number	Dimensions (mm)				Capacities						Weight (kg)
	Size (mm)		Land Diameters (mm)		Radial		Thrust		Torque (N-m)		
	Bore	OD	L1	L2	Dynami c	Static	Dynami c	Static	Dynami c	Static	
K05020 XP0	50	90	65	75.0	1845	1827	3999	2418	549	470	0.52
K02520 XP0	25	65	40	50.0	1518	1503	2545	1789	225	225	0.34
K36013 XP0	360	386	369.7	376.3	5688	2594	14220	4298	10403	3560	1.08
K34013 XP0	340	366	349.7	356.3	5365	2508	13412	4133	9286	3257	1.02
K32013 XP0	320	346	329.7	336.3	5042	2419	12605	3966	8232	2963	0.97
K30013 XP0	300	326	309.7	316.3	4719	2327	11796	3794	7242	2680	0.91
K25013 XP0	250	276	259.7	266.3	4008	2119	10019	3403	5168	2050	0.77
K20013 XP0	200	226	209.7	216.3	3232	1868	8080	2948	3375	1464	0.63
K19013 XP0	190	216	199.7	206.3	3038	1800	7595	2829	3024	1344	0.6
K18013 XP0	180	206	189.7	196.3	2909	1756	7272	2748	2753	1247	0.57
K17013 XP0	170	196	179.7	186.3	2780	1711	6949	2666	2494	1152	0.54
K16013 XP0	160	186	169.7	176.3	2586	1639	6464	2541	2193	1043	0.51
K15013 XP0	150	176	159.7	166.3	2456	1592	6141	2455	1963	954	0.48
K14013 XP0	140	166	149.7	156.3	2327	1544	5817	2368	1746	869	0.46
K13013 XP0	130	156	139.7	146.3	2133	1466	5333	2235	1496	771	0.43
K12013 XP0	120	146	129.7	136.3	2006	1415	5010	2144	1307	693	0.4
K11013 XP0	110	136	119.7	126.3	1875	1364	4686	2050	1131	617	0.37
K10013 XP0	100	126	109.7	116.3	1681	1279	4201	1906	931	532	0.34
K09013 XP0	90	116	99.7	106.3	1551	1224	3878	1808	784	464	0.31
K08013 XP0	80	106	89.7	96.3	1358	1133	3393	1653	619	388	0.28

Bearing Number	Dimensions (mm)				Capacities						Weight (kg)
	Size (mm)		Land Diameters (mm)		Radial		Thrust		Torque (N-m)		
	Bore	OD	L1	L2	Dynami c	Static	Dynami c	Static	Dynami c	Static	
K07013 XP0	70	96	79.7	86.3	1228	1074	3070	1547	500	328	0.26
K06013 XP0	60	86	69.7	76.3	1099	1014	2747	1436	393	272	0.23
K05013 XP0	50	76	59.7	66.3	919	910	2263	1226	280	211	0.2
K02513 XP0	25	51	34.7	41.3	696	689	1293	869	96	96	0.13
J17008X P0	170	186	176.55	179.42	1767	910	4418	1441	1543	596	0.2
J16008X P0	160	176	166.55	169.42	1666	878	4166	1386	1373	543	0.20
J15008X P0	150	166	156.55	159.42	1565	846	3914	1329	1213	492	0.20
J14008X P0	140	156	146.55	149.42	1465	812	3661	1271	1063	442	0.19
J13008X P0	130	146	136.55	139.42	1363	778	3156	1212	923	395	0.18
J12008X P0	120	136	126.55	129.42	1262	743	3156	1152	792	350	0.16
J11008X P0	110	126	116.55	119.42	1162	707	2903	1090	672	307	0.15
J10008X P0	100	116	106.55	109.42	1060	670	2651	1025	562	266	0.14
J09008X P0	90	106	96.55	99.42	959	631	2399	959	461	228	0.13
J08008X P0	80	96	86.55	89.42	859	591	2146	890	370	191	0.11
J07008X P0	70	86	76.55	79.42	757	549	1894	819	290	158	0.10
J06008X P0	60	76	66.55	69.42	656	506	1641	745	219	127	0.09
J05008X P0	50	66	56.55	59.42	555	460	1389	666	158	98	0.08
J02508X P0	25	41	31.55	34.42	334	331	758	469	49	40	0.06
K36008 XP0	360	376	365.9	370.1	3636	1396	9089	2330	6561	1890	0.46
K34008 XP0	340	356	345.9	350.1	3459	1350	8648	2255	5859	1728	0.42

Bearing Number	Dimensions (mm)				Capacities						Weight (kg)
	Size (mm)		Land Diameters (mm)		Radial		Thrust		Torque (N-m)		
	Bore	OD	L1	L2	Dynami c	Static	Dynami c	Static	Dynami c	Static	
K32008 XP0	320	336	325.9	330.1	3257	1310	8143	2166	5238	1580	0.39
K30008 XP0	300	266	305.9	310.1	3055	1261	7638	2076	4614	1429	0.35
K25008 XP0	250	266	255.9	260.1	2550	1133	6375	1840	3226	1075	0.28
K20008 XP0	200	216	205.9	210.1	2045	992	5113	1588	2086	759	0.22
K19008 XP0	190	206	195.9	200.1	1944	963	4860	1536	1888	701	0.21
K18008 XP0	180	196	185.9	190.1	1868	941	4671	1495	1722	651	0.21
K17008 XP0	170	186	175.9	180.1	1767	910	4418	1441	1543	596	0.2
K16008 XP0	160	176	165.9	170.1	1666	878	4166	1386	1373	543	0.2
K15008 XP0	150	166	155.9	160.1	1565	846	3914	1329	1213	492	0.2
K14008 XP0	140	156	145.9	150.1	1465	812	3661	1271	1063	442	0.19
K13008 XP0	130	146	135.9	140.1	1363	778	3156	1212	923	395	0.18
K12008 XP0	120	136	125.9	130.1	1262	743	3156	1152	792	350	0.16
K11008 XP0	110	126	115.9	120.1	1162	707	2903	1090	672	307	0.15
K10008 XP0	100	116	105.9	110.1	1060	670	2651	1025	562	266	0.14
K09008 XP0	90	106	95.9	100.1	959	631	2399	959	461	228	0.13
K08008 XP0	80	96	85.9	90.1	859	591	2146	890	370	191	0.11
K07008 XP0	70	86	75.9	80.1	757	549	1894	819	290	158	0.1
K06008 XP0	60	76	65.9	70.1	656	506	1641	745	219	127	0.09
K05008 XP0	50	66	55.9	60.1	555	460	1389	666	158	98	0.08
K02508 XP0	25	41	30.9	35.1	334	331	758	469	49	40	0.06