


Crossed Roller Bearing

CRBF full completement crossed roller bearings-



Boundary dimensions mm	
d	115
r 2min	CRBF11528A
r 1min	CRBF11528AUU
B	115
D	240
Identification number	
Sealed Type	28
Open Type	1.5
Shaft dia. mm	1.5
Mass (Ref.) kg	139
Basic static load rating C 0 N	12-M8 through 12- φ 9 through φ 14 counter bore de
Basic dynamic load rating C N	217
Mounting dimensions mm	
Da	12-φ9 through φ14 counter bore depth 13.5
d a	162
Mounting holes mm	
PCD1	198
Inner ring Mounting holes	84300
PCD2	138000
Outer ring Mounting holes	6.63

**CRBF Super Slim Crossed Roller Bearings** with mounting hole have an ultra-slim 5 mm bearing width□it's easy bolt-on mounting eliminates complex mounting procedures.Mounting Holed Type Super Slim Crossed Roller Bearings can be mounted directly to the mounting surface. No housing or pressure plate required.

CRBF Super Slim Crossed Roller Bearings with mounting hole have an ultra-slim 5 mm bearing width□it's easy bolt-on mounting eliminates complex mounting procedures.

Mounting Holed Type Super Slim Crossed Roller Bearings can be mounted directly to the mounting surface. No housing or pressure plate required.



### Mounting:

The shoulder height diameters ( $d_a$  and  $D_a$ ) which are related to mounting must meet the values shown in the dimension tables. When used with a housing, it is recommended to use a slight interference fit adjusted to the actual measured dimensions of the outer and inner ring. In addition, the depth of the housing bore is recommended to be equal to or larger than the bearing width. Mounting Holed Type Super Slim Crossed Roller Bearings have a plug hole for inserting cylindrical rollers. When mounting the bearings, position the plug away from the maximum load. The plug is located by the pin on the side.