

Tapered Roller Bearing

32300 Series Tapered Roller Bearing-



| | |
|-------------------------------------|-----------|
| Designation | 32308J2/Q |
| Principal dimensions [mm] | |
| d1 | 40 |
| D | 90 |
| B | 35.25 |
| Basic load ratings [kN] | |
| dyc(Cr) | 117 |
| stc(Cor) | 140 |
| Pu | 16 |
| Speed ratings [rpm] | |
| Speed Ratings | 5300 |
| Limiting Speed | 8000 |
| Weight(Kg) | 1.00 |
| ISO335 | |
| Dimensions (ABMA) | 2FD |
| Dimensions [mm] | |
| d | 40 |
| d1 | 62.9 |
| B | 33 |
| C | 27 |
| r1,2(min) | 2 |
| r3,4(min) | 1.5 |
| a | 23 |
| Abutment and fillet dimensions [mm] | |
| da(max) | 51 |
| db(min) | 49 |
| Da(min) | 73 |
| Da(max) | 81 |
| Db(min) | 82 |
| Ca(min) | 3 |
| Cb(min) | 8 |
| ra(max) | 2 |
| rb(max) | 1.5 |
| Value | |
| e | 0.35 |
| Y | 1.7 |
| Yo | 0.9 |